

## Product Information



### **650** UNISEX 'D' RING CHUKKA BOOTS

<b>DESCRIPTION</b>	UNISEX SAFETY BOOT. D RING CHUKKA DESIGN WITH PADDED TOPBAND. PENETRATION RESISTANT MIDSOLE. ANTI-STATIC DUAL DENSITY POLYURETHANE SOLE.
<b>COLOUR</b>	BLACK.
<b>SIZE RANGE</b>	3 TO 13 WHOLE SIZES.
<b>STANDARD</b>	MANUFACTURED TO COMPLY WITH BS EN345.
<b>PROTECTION CLASS</b>	S1 SAFETY BASIC - ANTI-STATIC - HEEL ENERGY ABSORPTION. PENETRATION RESISTANT MIDSOLE.
<b>UPPER MATERIALS</b>	UPPER - GRAINED FULL CHROME LEATHER. TOPBAND AND TONGUE - U COAGULATE.
<b>LINING MATERIALS</b>	VAMP LINING - NON WOVEN MATERIAL. QUARTER LINING - CAMBRELLE® 150 +2mm FOAM. BOTH MATERIALS PROVIDE COMFORT, ARE ABSORBENT, BREATHABLE, HARD WEARING AND RESISTANT TO ROT AND MILDEW.
<b>INTERLINING</b>	THE TOPLINE IS PADDED WITH FOAM FOR ADDITIONAL COMFORT.
<b>THREADS</b>	MADE FROM POLYESTER / COTTON.
<b>FASTENINGS</b>	5 D RING FASTENING. ALL RUST RESISTANT.
<b>INSOLE</b>	NON WOVEN ANTI-STATIC BOARD.
<b>HEEL REINFORCEMENT</b>	INTERNAL MOULDED THERMOPLASTIC STIFFENER FOR ADDITIONAL SUPPORT AND RIGIDITY AT THE HEEL.

<b>PENETRATION RESISTANT MIDSOLE</b>	<b>INTERNAL STEEL MIDSOLE. PROVIDES PROTECTION TO THE BOTTOM OF THE FOOT AGAINST PENETRATION BY SHARP OBJECTS SUCH AS NAILS - LEVEL OF PROTECTION 1100N.</b>
<b>INTERNAL TOE CAP</b>	<b>HARDENED RUST RESISTANT STEEL TOE CAP. PROVIDES PROTECTION AGAINST INJURY TO THE TOES CAUSED BY FALLING OBJECTS - LEVEL OF PROTECTION 200 JOULES. ALSO PROTECTION AGAINST COMPRESSION INJURY CAUSED BY THE TOES BEING TRAPPED UNDER A HEAVY OBJECT - LEVEL OF PROTECTION 15KN.</b>
<b>SOLE</b>	<b>DIRECT MOULDED DUAL DENSITY ANTI-STATIC POLYURETHANE.COMPRISING OF A LOW DENSITY LIGHTWEIGHT POLYURETHANE MIDSOLE TO PROVIDE COMFORT AND REDUCE MUSCLE FATIGUE AND A HARDWEARING SOLID POLYURETHANE OUTSOLE FOR DURABILITY AND ABRASION RESISTANCE.THE OUTSOLE HAS A CLEATED TREAD DESIGN TO IMPROVE GRIP.BOTH MIDSOLE AND OUTSOLE ARE OIL RESISTANT. THE SOLE FEATURES AN INTEGRAL SCUFF CAP TO PROTECT THE TOE OF THE FOOTWEAR. TO REDUCE INJURY CAUSED BY FALLING BACK ONTO THE HEEL, THE HEEL OF THE FOOTWEAR ABSORBS SOME OF THE ENERGY - LEVEL OF PROTECTION 20 JOULES.</b>
<b>ANTI-STATIC PROPERTIES</b>	<b>RANGE OF ELECTRICAL RESISTANCE 0.1 M ohm TO 1000 M ohm.</b>
<b>LACES</b>	<b>BLACK FLAT TAGGED WOVEN POLYESTER.</b>
<b>SOCK</b>	<b>BROWN CAMBRELLE® 150 COVERED ¾ FOOTBED.</b>